

## **ARCA ARK14126CHFL**



Order symbol: ARK14126CHFL EAN: 6418074097385 El. number:

Finland:

Product nbr: 8561562 Description: PC Enclosure Remarks: Hinged opaque flat cover

w/Plastic quick release latch. Base includes 1/2 and 3/4 inch

knock-outs

Including: Hinged cover. Base with 10-32 brass inserts, latched flat cover with formed in place PUR gasket, stainless hinge pin. Base with 1/2 and 3/4 inch knock-outs. Quick release latches. Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.

#### Sample photo

Dimensions:	Length	Width	Height	Accessories:	
mm:	305	254	127	ALBP1412	Aluminum Back Panel
inch:	12.0	10.0	5.0	ADFP1412	Dead Front Panel w/ screws
	12.0	10.0	0.0	ASP1412	Aluminum Swing Panel
Materials:				ASPK1412	Swing Panel Kit incl. Panel
Material:	Polycarbo	nate		ASPHK14	Swing Panel Kit w/o Panel

Base colour: RAL 7035 -light grey Cover screws material: Stainless steel

Cover colour: RAL 7035 -light grey Gasket material: Polyurethane

## Temperatures:

Temperature °C (short term): -40 ... 140 °C Temperature °C (continuous): -40 ... 80 °C Temperature °F (short term): -40 ... 284 °F -40 ... 175 °F Temperature °F (continuous):

## Accessories:

ABP1412 Painted Steel Back Panel

ALBP1412	Aluminum Back Panel	
ADFP1412	Dead Front Panel w/ screws	
ASP1412	Aluminum Swing Panel	
ASPK1412	Swing Panel Kit incl. Panel	
ASPHK14	Swing Panel Kit w/o Panel	
AMFL12	12" Mounting Flange Set	

## Rating

Ingress Protection (EN 60529): IP66/IP67 Impact Resistance (EN 62262): IK09 Electrical insulation: Totally insulated Halogen free (DIN/VDE 0472, Part 815): 1

UV resistance: UL 508 Flammability Rating: UL 508 Glow Wire Test (IEC 695-2-1) °C: 960

NEMA Class: NEMA 4, 4X, 12 and 13

# Certificates:

Gost R

