

# **ARCA ARK14127CHTSST**

Order symbol: ARK14127CHTSST EAN: 6418074097835

Product nbr:8561607El. number:Description:PC EnclosureFinland:

Remarks: Hinged transparent cover w/S.S. Lockable twist latch. Base includes 1/2 and 3/4 inch

knock-outs.

Including: Screw cover. Base with 10-32 brass inserts, cover with formed in place PUR gasket and 4 stainless cover screws. Base includes 1/2 and 3/4 inch knock-outs. Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.

| Dimensions: | Length | Width | Height |
|-------------|--------|-------|--------|
| mm:         | 356    | 305   | 178    |
| inch:       | 14.0   | 12.0  | 7.0    |

### **Materials**

Material:PolycarbonateBase colour:RAL 7035 -light greyCover screws material:Stainless steelCover colour:Clear transparentGasket material:Polyurethane

### Temperatures:

Temperature °C (short term): -40 ... 140 °C

Temperature °C (continuous): -40 ... 80 °C

Temperature °F (short term): -40 ... 284 °F

Temperature °F (continuous): -40 ... 175 °F

## Accessories:

ABP1412 Painted Steel Back Panel

| Accessories: |                             |
|--------------|-----------------------------|
| ALBP1412     | Aluminum Back Panel         |
| ADFP1412     | Dead Front Panel w/ screws  |
| ASP1412      | Aluminum Swing Panel        |
| ASPK1412     | Swing Panel Kit incl. Panel |
| ASPHK14      | Swing Panel Kit w/o Panel   |
| AMFL12       | 12" Mounting Flange Set     |
|              |                             |

### Rating:

Ingress Protection (EN 60529): IP66/IP67 Impact Resistance (EN 62262): IK09 Electrical insulation: Totally insulated Halogen free (DIN/VDE 0472, Part 815): 1

UV resistance: UL 508 Flammability Rating: UL 508

Glow Wire Test (IEC 695-2-1) °C: 960 NEMA Class: NEMA 4, 4X, 12 and 13

