



**Product #:** 8143031

**Order Symbol:** UL CAB PC 203018 T

**Description:** 7.9 x 11.8 x 7.1 inch polycarbonate enclosure with a Smoked transparent door, and latches on the short side

| Dimensions | Height | Width | Depth |
|------------|--------|-------|-------|
| Inch       | 7.9    | 11.8  | 7.1   |
| mm         | 200    | 300   | 180   |

| Materials        |                      |
|------------------|----------------------|
| Material:        | Polycarbonate        |
| Base color:      | RAL 7035 -light grey |
| Cover color:     | Transparent          |
| Gasket material: | Polyurethane         |

| Temperatures                 |             |
|------------------------------|-------------|
| Temperature °F (short term): | -40 ... 250 |
| Temperature °F (continuous): | -40 ... 175 |
| Temperature °C (short term): | -40 ... 140 |
| Temperature °C (continuous): | -40 ... 80  |

| Ratings                                |                                    |
|--|------------------------------------|
| Ingress Protection (EN 60529):         | IP65                               |
| Impact Resistance (EN 62262):          | IK08                               |
| Electrical insulation:                 | Totally insulated                  |
| Halogen free (DIN/VDE 0472, Part 815): | No                                 |
| UV resistance:                         | UL 508                             |
| Flammability Rating:                   | UL94-5VA (f1)/ Cover: UL94-V0 (f1) |
| Glow Wire Test (IEC 60695):            | 960 °C                             |
| UL/cUL Type:                           | Type 1, 4, 4X, 12, and 13          |