



Product #: 7032560
Order Symbol: UL PC 080807
Description: Enclosure, PC
Remarks: Grey cover

| Dimensions | Height | Width | Depth |
|------------|--------|-------|-------|
| Inch | 3.2 | 3.1 | 2.6 |
| mm | 82 | 80 | 65 |

| Materials | |
|------------------|----------------------|
| Material: | Polycarbonate |
| Base color: | RAL 7035 -light grey |
| Cover color: | RAL 7035 -light grey |
| Gasket material: | Polyurethane |

| Temperatures | |
|------------------------------|-------------|
| Temperature °F (short term): | -40 ... 250 |
| Temperature °F (continuous): | -40 ... 175 |
| Temperature °C (short term): | -40 ... 120 |
| Temperature °C (continuous): | -40 ... 80 |

| Ratings | |
|--|-------------------------------|
| Ingress Protection (EN 60529): | IP66IP67 |
| Impact Resistance (EN 62262): | IK07IK08 |
| Electrical insulation: | Totally insulated |
| Halogen free (DIN/VDE 0472, Part 815): | No |
| UV resistance: | UL 508 |
| Flammability Rating: | UL 746C 5" |
| Glow Wire Test (IEC 60695): | 960 °C |
| UL/cUL Type: | NEMA Type 1, 4, 4X, 12 and 13 |