



Product #: 5824023

Order Symbol: UL TPCM 131308

Description: Enclosure, PC

Remarks: Grey Cover with Metric Knock-Out Base

| Dimensions | Height | Width | Depth |
|------------|--------|-------|-------|
| Inch | 5.1 | 5.1 | 3 |
| mm | 130 | 130 | 75 |

Materials

| | |
|------------------|----------------------|
| Material: | Polycarbonate |
| Base color: | RAL 7035 -light grey |
| Cover color: | RAL 7035 -light grey |
| Gasket material: | Polyurethane |

Temperatures

| | |
|------------------------------|-------------|
| Temperature °F (short term): | -40 ... 250 |
| Temperature °F (continuous): | -40 ... 175 |
| Temperature °C (short term): | -40 ... 140 |
| Temperature °C (continuous): | -40 ... 80 |

Ratings

| | |
|--|------------------------------------|
| Impact Resistance (EN 62262): | IK07/IK08 |
| Electrical insulation: | Totally insulated |
| Halogen free (DIN/VDE 0472, Part 815): | No |
| UV resistance: | UL 508 |
| Flammability Rating: | UL94-5VA (f1)/ Cover: UL94-V0 (f1) |
| Glow Wire Test (IEC 60695): | 960 °C |
| UL/cUL Type: | 1, 4, & 4X |