



AMERICAN ZETTLER, INC.

75 COLUMBIA • ALISO VIEJO, CA 92656 • TEL: 949-831-5000 • FAX: 949-831-8642

• WEB SITE: [HTTP://WWW.AZETTLER.COM](http://www.azettler.com) • E-MAIL: sales@azettler.com

For Immediate Release

March 5, 2007

AZ762F Series **20 A SPST Miniature Power Relay with Quick Connects**

Contact: Fred Harmon
Vice President, Sales & Marketing
(949) 831-5000

Aliso Viejo, California - American Zettler Inc. has just announced a new extra high temperature version of their AZ762 relay. The new relay, designated AZ762F, is rated by UL for 20 A, 277 VAC, 100k cycles. The AZ762F SPST relay features quick connects for the load connection so there is no need for heavy copper traces on the PCB. The Quick Connects are available either vertically or horizontally oriented. With isolation of 10 mm and a dielectric strength of 5000 Vrms, this relay is perfect for many HVAC and white goods applications where high ambient temperatures (up to 125°C) might pose a problem for other relays. The AZ762F is RoHS compliant and has full UL / CUR/ VDE approvals.



AMERICAN ZETTLER, INC.

75 COLUMBIA • ALISO VIEJO, CA 92656 • TEL: 949-831-5000 • FAX: 949-831-8642

• WEB SITE: [HTTP://WWW.AZETTLER.COM](http://www.azettler.com) • E-MAIL: sales@azettler.com

RELAY PROFILE

Relay

AZ762F

Relay Description

20 A SPST Miniature Power Relay with Quick-Connects

Features/Benefits

Dielectric strength 5000 Vrms, 10kV surge, 20 Amp switching, Class F (155°C) standard, Isolation spacing greater than 10mm, UL, CUR, VDE

Relay Applications

HVAC, lamp and motor controls for office equipment, space heater controls, microwave oven (magnetron) controls, range controls



AMERICAN ZETTLER, INC.

75 COLUMBIA • ALISO VIEJO, CA 92656 • TEL: 949-831-5000 • FAX: 949-831-8642

• WEB SITE: [HTTP://WWW.AZETTLER.COM](http://www.azettler.com) • E-MAIL: sales@azettler.com

CROSS REFERENCE

Tyco V23077

Song Chuan 881 WP

Finder 45