

AZ9402

10 AMP MINIATURE POWER RELAY

FEATURES

- 10 Amp switching capability
- SPST-N.O. and SPDT configurations
- Epoxy sealed version available
- UL, CUR E44211
- TUV pending



CONTACTS

Arrangement	SPST N.O. (1 Form A) SPDT (1 Form C)
Ratings	Resistive load: Max. switched power: 150 W or 1250 VA N.O. Max. switched current: 10 A Max. switched voltage: 30 VDC* or 277 VAC *Note: If switching voltage is greater than 30 VDC, special precautions must be taken. Please contact the factory.
UL, CUR	5A at 250 VAC 10A at 125 VAC 4.2A at 277 VAC 1/4 HP at 120/240/277 VAC TV- 5 at 120 VAC Pilot Duty at 24 VA, 24 VAC ;125 VA at 120/240/277 VAC ; C150 at 120 VAC
TUV	5A at 250 VAC 5A at 28 VDC
Material	Silver Nickel
Resistance	< 0.1 Ohm (24 V, 1 A voltage drop method)

COIL

Power At Pickup Voltage (typical)	253 mW (Standard Coil) 113 mW (Sensitive Coil)
Max. Continuous Dissipation	1.25 W at 20°C (68°F)
Temperature Rise	40°C (72°F) (Standard Coil) 20°C (36°F) (Sensitive Coil)
Temperature	Max. 105°C (221°F)

GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 1 x 10 ⁷ 1 x 10 ⁵ at 10 A 120 VAC Res.
Operate Time (max.)	8 ms at nominal coil voltage
Release Time (max.)	5 ms at nominal coil voltage (with no coil suppression)
Dielectric Strength (at sea level for 1 min.)	1000 Vrms contact to contact 4000 Vrms contact to coil
Insulation Resistance	1 x 10 ⁹ ohms minimum at 500 VDC
Dropout	Greater than 5% of nominal coil voltage
Ambient Temperature Operating	At nominal coil voltage -40°C (-40°F) to 70°C (158°F)
Storage	-40°C (-40°F) to 130°C (266°F)
Vibration	0.062" DA at 10–55 Hz
Shock Mechanical	100 g for 11 ms 1/2 sine pulse
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	270°C (518°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	7 grams

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.



AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

11/13/08W

AZ9402

RELAY ORDERING DATA

COIL SPECIFICATIONS – Standard Coil (SPDT and SPST)				ORDER NUMBER*	
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance $\pm 10\%$	SPST-NO	SPDT
3	2.25	3.3	20	AZ9402-1A-3D	AZ9402-1C-3D
5	3.75	5.5	56	AZ9402-1A-5D	AZ9402-1C-5D
6	4.5	6.6	80	AZ9402-1A-6D	AZ9402-1C-6D
9	6.75	9.9	180	AZ9402-1A-9D	AZ9402-1C-9D
12	9.0	13.2	320	AZ9402-1A-12D	AZ9402-1C-12D
18	13.5	19.8	720	AZ9402-1A-18D	AZ9402-1C-18D
24	18.0	26.4	1280	AZ9402-1A-24D	AZ9402-1C-24D

*Add suffix "E" for sealed version

COIL SPECIFICATIONS – Sensitive Coil (SPST)				ORDER NUMBER**	
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance $\pm 10\%$	Unsealed	Sealed
3	2.25	3.3	45	AZ9402-1A-3DS	AZ9402-1A-3DSE
5	3.75	5.5	125	AZ9402-1A-5DS	AZ9402-1A-5DSE
6	4.5	6.6	180	AZ9402-1A-6DS	AZ9402-1A-6DSE
9	6.75	9.9	405	AZ9402-1A-9DS	AZ9402-1A-9DSE
12	9.0	13.2	720	AZ9402-1A-12DS	AZ9402-1A-12DSE
18	13.5	19.8	1620	AZ9402-1A-18DS	AZ9402-1A-18DSE
24	18.0	26.4	2880	AZ9402-1A-24DS	AZ9402-1A-24DSE

**For 1 Form C substitute "-1C" for "-1A"

MECHANICAL DATA

PC BOARD LAYOUT

*omitted from Form A

WIRING DIAGRAM

VIEWED TOWARD TERMINALS

Dimensions in inches with metric equivalents in parentheses. Tolerance: $\pm .010$ "



AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

11/13/08W