



Quality Products. Service Excellence.

Type 4, 4X Stainless Steel Pushbutton Enclosures 1437SS Series

Extra Deep



Application

- Designed to accept standard heavy duty oil tight pushbuttons, switches and pilot lights.
- Provides protection from dirt, dust, oil and water.

Standards

- UL 508A Type 4 and 4X
- CSA Enclosure 4 and 4X
- **Complies with**
 - NEMA Type 4 and 4X
 - IEC 60529, IP66
- Appropriate components are required to maintain these standards.

Construction

- Formed from 14 gauge steel except A which is 16 gauge.
- Smooth continuously welded seams.
- Welded brackets provide for enclosure mounting.
- Captive cover screws fasten into threaded, sealed wells.
- Larger enclosures provide internally hinged removable covers, designed to hold the cover open during wiring (see drawings).
- Oil resistant gasket and adhesive.
- A bonding stud is provided on the door and a grounding stud is provided on the enclosure.

Finish

- Natural stainless steel with a smooth brushed finish.

Accessories

- Hole Plugs
- Bonding Wire Kits

New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

| 304 S.S. 22.5mm PB Part No. | 304 S.S. 30.5mm PB Part No. | 316 S.S. 22.5mm PB Part No. | 316 S.S. 30.5mm PB Part No. | No. Of Holes | Enclosure | | |
|-----------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|--------------------|-----------|------|------|
| | | | | | H | W | D |
| 1437MSSA ¹ | 1437SSA ¹ | 1437MS16A ¹ | 1437S16A ¹ | 1 | 4.00 | 4.00 | 4.75 |
| 1437MSSB | 1437SSB | 1437MS16B | 1437S16B | 2 | 6.00 | 4.00 | 4.75 |

Type 4, 4X Stainless Steel Pushbutton Enclosures (1437SS Series) - Hammond Mfg.

| 304 S.S. 22.5mm PB Part No. | 304 S.S. 30.5mm PB Part No. | 316 S.S. 22.5mm PB Part No. | 316 S.S. 30.5mm PB Part No. | No. Of Holes | Enclosure | | |
|-----------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|--------------------|-----------|-------|------|
| | | | | H | W | D | |
| 1437MSSC | 1437SSC | 1437MS16C | 1437S16C | 3 | 8.00 | 4.00 | 4.75 |
| 1437MSSD | 1437SSD | 1437MS16D | 1437S16D | 4 | 10.00 | 4.00 | 4.75 |
| - | 1437SSS | - | 1437S16S | 16 | 11.75 | 10.75 | 4.75 |

¹ Not hinged

Data subject to change without notice

© 2022. Hammond Manufacturing Ltd. All rights reserved.