Quality Products. Service Excellence.

Rack Mount Metered PDU 1589-AM Series

20A | Single-Phase 125V | Front or Rear Facing 5-15/20R Outlets

Features



- Panel dimensions are 1.75" high (1U) and 19" rack width.
- Available with a rocker switch or red pilot light to indicate power on.
- The 20 amp. series uses heavy 12 gauge wire cord 12/3 SJT for extreme temperature ranges and integral NEMA 5-20P straight blade or L5-20P locking type moulded plug.

Specifications

- Includes 20 Amp, 125 VAC circuit breaker to prevent accidental overload.
- Unit includes easy to read 0.37" high, red LED ammeter (1.38" x 0.88" display).
- Digital ammeter accuracy +/- 0.1 Amps
- UL/cUL recognized Standard UL1363 file No. E166039 & CSA C22.2 No. 308-14
- Operating temperature is from -20 degrees C to +60 degrees C
- Finished in textured RAL9005 black powder paint finish.
- TAA-compliant for GSA Schedule purchases.
- RoHS and REACH compliant.
- · Manufactured in North America.

Plug Types







L5-20P Locking Type

Accessories

Mounting Hardware

Rail Depth Adapter Kit















| | Illuminated | | | | Number | Number | | | | | |
|----------------|----------------|---------------------------|-------|-------|------------|------------|-----------|-------------|------------|-----------|-------|
| On/Off Switch | Light Only | Overall Dimensions | | | of Outlets | of Outlets | Outlet | Cord | Plug | NEMA | Rack |
| Part No. | Part No. | Height | Width | Depth | On Front | On Rear | NEMA Type | Length (ft) | Blade Type | Plug Type | Units |
| 1589H6C1BKRFAM | 1589T6C1BKRFAM | 1.72 | 19.00 | 2.66 | 6 | 0 | 5-20R | 6 | Locking | L5-20P | 1U |

| | Illuminated | | | | Number | Number | | | | | |
|----------------|----------------|---------------------------|-------|-------|------------|------------|-----------|-------------|------------|-----------|-------|
| On/Off Switch | Light Only | Overall Dimensions | | | of Outlets | of Outlets | Outlet | Cord | Plug | NEMA | Rack |
| Part No. | Part No. | Height | Width | Depth | On Front | On Rear | NEMA Type | Length (ft) | Blade Type | Plug Type | Units |
| 1589H6F1BKRFAM | 1589T6F1BKRFAM | 1.72 | 19.00 | 2.66 | 6 | 0 | 5-20R | 6 | Straight | 5-20P | 1U |
| 1589H6C1BKRRAM | 1589T6C1BKRRAM | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-20R | 6 | Locking | L5-20P | 1U |
| 1589H6F1BKRRAM | 1589T6F1BKRRAM | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-20R | 6 | Straight | 5-20P | 1U |

Data subject to change without notice

© 2022. Hammond Manufacturing Ltd. All rights reserved.