

## Dimensions (mm)




Figure 1. CRR physical layout

### Features

- High quality and reliability
- Very small size
- Ability to switch up to 1 amp
- Insulation resistance > 10<sup>12</sup> Ohms
- Capable of switching and carrying up to 2 GHz
- Dielectric strength across the contacts 200 volts
- Low offset voltage < 1μV
- Contacts dynamically tested
- Low stable contact resistance
- Long life with up to a billion reliable operations

### Applications

- Ideal for use in testers and Automatic Test Equipment that test the functionality of all sizes of printed circuit boards.

## Introduction

Functional PCB testers test printed circuit boards as large as 600 mm by 600 mm (or 2 foot square). These boards are in some cases, up to 20 layers thick, requiring 1000s of test points for functional verification. Each one of these test points may require as many as 6 switches each to provide the various voltages and currents for proper measurement. Because of size restrictions, isolation, relatively fast acting and good RF characteristics, reed relays are often chosen as the testing switch. A fully loaded tester can therefore, house over 20,000 reed relays. If there is one relay failure, this is equivalent to a failure level of 50 part per million (PPM). So the quality and reliability must reign supreme. MEDER's reed relays have stepped up to meet these requirements; and their relays have become an accepted standard in the Automatic Test Equipment (ATE) industry.




Figure 2. Reed relay signals pass/fail test results on functional PCB test.

## Reed Relays are a Key Component in ATE Testers Testing Functional PCBs

Almost every piece of electronic equipment today uses printed circuit boards (PCBs). These PCBs range from a few square mm (0.08 square inches) to as large as 600 mm by 600 mm (2 ft by 2 ft ). These PCBs can have only a few components to as many as thousands of components. On the larger PCBs there may be 1000s of test points that need their functionality determined. These usually work in conjunction with a bed of nails tester. This allows for the direct hook up to all the test points. Each one of these test points will need up to 6 switches to correctly switch in different voltages, currents and determine functionality. Semiconductor switches offer too much leakage, lack isolation and can interact with the actual test being undertaken. Electromechanical relays become unreliable after 1 million cycles. Reed relays make the best choice. MEDER offers several reed relay series that represent a technically savvy low cost solution.

## Specifications

CRR Series	Min	Norm	Max	Units
Operate Specs (@20°C)				
<b>Coil Characteristics*</b>				
Coil Resistance	135	150	165	Ohms
Coil Voltage		5.0		Volts
Max Pull-in Voltage			3.75	Volts
Min. Drop-out	0.85			Volts
<b>Reed Switch Characteristics</b>				
Contact rating			10	Watts
Switching voltage	0		170	Volts
Switching current	0		0.5	Amps
Carry current	0		0.5	Amps
Max Carry Current for 5 Ms			2.0	Amps
DC Static contact resistance			250	mOhms
Dynamic contact resistance			250	mOhms
Dielectric voltage across contacts	210			Volts
Dielectric voltage from coil to contacts	1000			Volts
Operate time (w/ 40% overdrive min)			0.1	msec
Release time (no coil suppression)			20	µsec
Operate Temperature	-20		100	°C
Storage Temperature	-55		125	°C

\*Coil parameters will vary by 0.2% /°C

MEDER offers both standard through hole and surface mount in very small packages. All relays come with magnetic shielding allowing for very close packaging. Our surface mount CRR series can switch and carry DC to 2 GHz signals for use in high frequency requirements or fast digital pulses. Our standard SIL and MS in-line pin layouts are both considered standards in the industry and meet the stringent conditions for high quality and reliability. All series can carry up to 1 amp and hold off 200 Volts across the contacts.

MEDER's reed relays use hermetically sealed reed switches that are further packaged in strong high strength thermoset molding compound, and can therefore be subject to various environments without any loss of reliability.

The reed relay is an excellent choice because it can operate reliably over a wide temperature range, and represents an economical way to carry out billions of switching operations.

### Through Hole Series

Relay Series	Dimensions		Illustration	
	mm	inches		
MS	W	3.80	0.150	
	H	6.80	0.268	
	L	15.20	0.598	
SIL	W	5.08	0.200	
	H	7.8	0.307	
	L	19.8	0.780	

### Surface Mount Series

Relay Series	Dimensions		Illustration	
	mm	inches		
SRR	W	4.0	0.157	
	H	3.2	0.126	
	L	7.5	0.295	
CRR	W	4.4	0.173	
	H	3.5	0.137	
	L	8.6	0.338	

\*\*Consult the factory for more options not listed above.